

# MG 10/6 S-R



Control panel



Central lifting eye



10,5 lt Fuel Tank

We offer now what others will do tomorrow.



**Genset s.p.a.**

Via Stazione 5 - 27030  
Villanova d'Ardenghi (PV) - Italy  
Phone: +39-0382-5091

commerciale@genset.it  
www.genset.it

 **GenSet**  
Next Gen technology  
for top business.

**SILENCED POWER GENERATOR**

**OUTPUT POWER 10 KVA THREE-PHASE AND 8,3 KVA SINGLE-PHASE**

**3000 RPM DIESEL ENGINE**

**10,5 LT FUEL TANK**

<p><b>Standard Features</b></p>	<ul style="list-style-type: none"> <li>• Voltmeter</li> <li>• Hourmeter</li> <li>• Earth leakage circuit breaker</li> <li>• Emergency stop button</li> <li>• Starter battery</li> <li>• 1 x 16 A, 400 V - 50 Hz EEC three-phase socket</li> <li>• 1 x 32A, 230V - 50 Hz EEC single-phase socket</li> <li>• 1 x 16A, 230V - 50 Hz EEC single-phase socket</li> <li>• Power output protection</li> <li>• Fitted for AMF/ATS or Remote control operation</li> <li>• Voltage switch</li> <li>• Central lifting eye</li> </ul>
<p><b>Options</b> available as factory options</p>	<ul style="list-style-type: none"> <li>• Versions with different voltages</li> <li>• Automatic voltage regulator (AVR)</li> </ul>
<p><b>Accessories</b> on request</p>	<ul style="list-style-type: none"> <li>• AMF/ATS panel for auto start operation</li> <li>• Trolley: two-wheels and handles</li> <li>• Remote START/STOP kit</li> </ul>
<p><b>Noise level</b></p>	<ul style="list-style-type: none"> <li>• Lwa 97 (72 dB a 7 mt)</li> </ul>
<p><b>AC generator - 50Hz</b></p>	<ul style="list-style-type: none"> <li>• Type: synchronous</li> <li>• Three-phase power (max.): 10 kVA - 400 V</li> <li>• Single-phase power (max.): 8,3 kVA - 230 V</li> <li>• Power Factor: <math>\cos \phi</math> 0,8</li> </ul>
<p><b>Diesel Engine</b> 3000 rpm</p>	<ul style="list-style-type: none"> <li>• Type: Lombardini 25LD330/2 - 2 cyl. - 12,6 hp (9,3 kWm) - 654 cm<sup>3</sup></li> <li>• Cooling system: air</li> <li>• Starting system: electric</li> <li>• Fuel tank capacity: 10,5 lt</li> <li>• Fuel consumption @ 75%: 2,2 lt/h</li> </ul>
<p><b>Other features</b></p>	<ul style="list-style-type: none"> <li>• Insulation Class: H</li> <li>• Ambient temperature: 40 °C (*)</li> <li>• Altitude: 1000 mt (*)</li> <li>• Mechanical Protection: IP 23</li> <li>• Dimensions (L x W x H): 1000 x 560 x 730 mm</li> <li>• Dry weight: 190 kg</li> </ul>

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.  
In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.